



TENAX S.p.A. – 37020 Volargne (VR) – Italy – Via 1° Maggio, 226/263

Tel. +39 045 686 0222 – Fax +39 045 686 2456

<mailto:tenax@tenax.it> - <http://www.tenax.it/>



06/05/1999

TECHNICAL INFORMATION

Product name WATER-BASED WATERPROOFING SKUDO FOR GRANITE

Application It is suitable to protect granites both for indoor and outdoor
It does not causes colours' changes.

TECHNICAL DATA

Density at 25°C gr/cm ³	1
Aspect	yellowish transparent liquid
Standard colour	no colour
Packing litres	1 20
Storing time: if stored at temperature between 40°C and 0°C in the original tins away from bad weather Skudo will last 1 year	
Important: as it is water-based, Skudo freezes at temperatures below 0°C	

SKUDO WATERPROOFING for granite operates on the surfaces of materials, it stops microporosities so that prevents liquids from penetrating the material but it remains permeable to vapours letting materials breath and keeping their characteristics unchanged. Skudo neither creates superficial films nor causes colours' changes.

Instruction for use Material should be dry and free from dust and grease, SKUDO may be applied with a cloth.
A better result will be reached after at least two coats of sealer, with a 30 minutes' interval from each application; clean with a cloth after 20 minutes from the last application.

Important When a surface is treated for the first time, it is worth to test it on a sample or a hidden surface.

Quantity to be used 1 litre of SKUDO is generally enough for 10/15sqm but, of course, the necessary quantity depends on the materials' porosity.

Safety measures SKUDO is a chemical product. We suggest to follow sanitary regulations as specified in our safeness data form.

The details given above are for information and reference purposes only. Tenax S.p.a. reserves the right to make changes to this Data Sheet at any time without giving prior notice.